





J-260-ND-SL

MODEL J-260-ND-SL
DOUBLE SIDE
SLOTTED FLEXMOUNT
Ø63mm = SF2




MODEL J-260-ND-SL Slotted Flex Mounts


MODEL J-260-ND-SL DOUBLE SIDE
SLOTTED FLEXMOUNT Ø46mm = SF1




MODEL J-260-ND-SL DOUBLE SIDE
SLOTTED FLEXMOUNT Ø66mm = SF3



MODEL J-260-ND-SL SINGLE SIDE
SLOTTED FLEXMOUNT Ø27mm TO 46mm = SF4



MODEL J-260-ND-SL SINGLE SIDE
SLOTTED FLEXMOUNT Ø38mm TO 79mm = SF5



All dimensions are in mm with a tolerance of ±0.1 unless otherwise specified



- Robust hollow shaft encoder
- Ideally suited for induction motor

Channels

R = ABZ / Q = AB / A = A

Output

- HV = Driver (10mA Source / Sink) without inverted channels
- HVLD = Driver (10mA Source/Sink) with inverted channels
- PP = Driver (50mA Source/Sink) without inverted channels
- PPLD/HTL = Driver (50mA Source/Sink) with inverted channels
- OC = Open Collector without inverted channels
- TTL/RS422 = Driver (10mA Source/Sink) with inverted channels at 5vdc

PPR

see ppr option below

Voltage

V1 = 5 VDC / V2 = 10-28 VDC / V3 = 5-28 VDC

Shaft Bore

6 = 6mm / 6.35 = 6.35mm / 8 = 8mm / 10 = 10mm /

Size Ø d

12 = 12mm / 14 = 14mm / X = Special

Bore Style

B = Blind Hollow Shaft / T = Through Hollow Shaft

Mounting

SF1 = Double Side Slotted Flexmount 46mm

Options

- SF2 = Double Side Slotted Flexmount 63mm
- SF3 = Double Side Slotted Flexmount 66mm
- SF4 = Single Side Slotted Flexmount 27mm To 46mm
- SF5 = Single Side Slotted Flexmount 38mm To 79mm

Clamping Style

- FS = Front Side
- RS = Rear Side

Protection

1 = IP50 / 2 = IP65 (For Blind Hollow Only)

Temperature

S = 0-70°C / H = 0-100°C

Connection Location

SG = Side Gland Only

CE Certified

N = Standard / CE = CE Certified

Ordering Example – J-260-ND-SL-R-HVLD-1000-V2-6-B-SF2-FS-1-S-SG-N

Model J-260-ND-SL PPR Options

1,2,3,4,5,6,8,9,10,12,14,15,16,18,20,22,24,25,26,28,30,31,32,33,34,36,38,40,42,45,46,48,50,54,55, 60,64,72,76,80,82,84,86,88,90,92,94,95,96,98,100,106,108,110,112,114,120,122,125,128,130,136, 144,146,148,150,156,157,160,164,170,171,172,176,180,200,210,240,250,256,276,300,305, 360,480,500,512,597,600,720,750,800,840,960,1000,1024,1080,1200,1250,1270,1500,2000,2048, 2500,3000,4096,5000,6000,7200,8192 & 10000